

LED NEMA4X/NSF REMOTE HEAD

FEATURES

- Two fully adjustable, ultra bright 3.3 watt high performance MR-16 base LED lamp heads for optimized center-to-center spacing..
- Powered from low voltage 6V/12V DC power source with low voltage wiring (not provided).
- Housing is reinforced polycarbonate construction in white or black finish.
- Corrosion-resistant enclosure with one piece, high-impact resistant, UV stabilized polycarbonate lens and molded gasket with stainless steel screws.
- Knockouts provided for conduit feed applications.
- OPTION: TP: Tamper-proof hardware helps discourage unauthorized access to the unit.

MOUNTING

- Universal knockout pattern on back provided with gasket for watertight seal for back mount.
- Distance of maximum run is determined by system voltage, wire gauge and total maximum wattage on the run.
- Suitable for wall or ceiling mount.

FIXTURE COMPATIBILITY TABLE

Refer to individual specification sheets to confirm remote load capacity

EBU & EXIT MODELS			
CAD	CAL	CAR	CWL
DXR	RMR	CEM	IND
HLE	HLC		
CENTRAL BATTERY MODELS			
CBM	CBL	CBE	

CODES

- UL Listed with approved Signtex Products.
- IP66 rated for Ingress protection.
- NEMA4X rated..
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL certified for use in food service operations.

WARRANTY

- 5 year total customer satisfaction warranty.
For details see Signtex product catalog technical data section.

FIXTURE ORDERING INFORMATION EXAMPLE: *INDRB2B-TP*

IND	RB	2	B	TP
SERIES	OPERATION	LAMP HEADS	COLOR	OPTIONS
IND	RB Powered from EBU or EXIT Combo	1 Single Head	W White	TP Tamper-proof
	RE Powered from Central Battery System	2 Double Head	B Black	

PROJECT:

TYPE:

CATALOG #:

PATHLITE
Series IND
REV #: IND.09.25.01



STANDARD



OPTIONAL



DIMENSIONS

