

Project:	
Type:	
Catalog #:	

### STANDARD



### OPTIONAL



### ILLUMINATION

- Two fully adjustable, ultra bright 3.3 watt high performance MR-16 base LED lamp heads for optimized center-to-center spacing.

### ELECTRICAL

- Powered from low voltage 6V/12V DC power source with low voltage wiring (not provided).

### MOUNTING

- Die-cast mounting brackets provided for surface wall-mount installation.
- Distance of maximum run is determined by system voltage, wire gauge and total maximum wattage on the run.

### HOUSING

- Housing is fiberglass reinforced construction in gray finish.
- Corrosion-resistant enclosure with one piece, high-impact resistant, UV stabilized polycarbonate lens and molded gasket with stainless steel screws.


### OPTIONS

- TP: Tamper-proof hardware helps discourage unauthorized access to the unit.

### WARRANTY / LISTING

- Five year warranty.
- UL listed with approved Best Lighting Products.
- IP66 rated for Ingress protection.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- Rated for Class 1, Division 2, Groups A, B, C, and D.

### DIMENSIONS



### FIXTURE COMPATIBILITY CHART

Reference individual unit equipment specification sheets for remote load capacity availability.

BEST LIGHTING MODEL TYPE			
CADXR	CALEDXTE	CAR	CWLEZXTE-RC
DXR	LEDSDXR	LEDTFX-2	NYDXR
RMR-16-65/125	CEMXTE	INDEMR	HLEMR
INDCWLEZ	HLCWLEZ	CAEM	HLCWLEZU

### ORDERING INFORMATION

Sample Part Number: **HLRHLED16-1G**

MODEL	HEADS	HOUSING COLOR	OPTIONS
HLRHLED16	1 2	Single Twin	G Gray
			TP Tamper-Proof