

Die-Cast Aluminum Exit Sign

FEATURES

- Ultra bright, energy efficient, long life Red or Green LEDs.
- Premium-grade, die-cast aluminum housing (also available in optional black or white powder-coated finishes).
- Field selectable knockout Chevron directional indicators.
- Unique design allows double face conversion in the field.
- Quick-snap face plate closure.
- Aluminum mounting canopy included for top or end mount.
- Universal knockout pattern on back plate for wall mount.
- SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meets electrical and life safety codes.
- 2C-120V/2C-277V: Dual circuit option on the AC-only unit enables it to be connected to two different power supplies at the same time.
- TP: Tamper-proof hardware helps discourage unauthorized access to the unit.
- USA: Substantial transformation assembly in the U.S. complies with "Assembled in the USA" under the Buy American Act

ELECTRICAL

- Dual 120V/277 voltage.
- Charge rate/power "ON" LED indicator light and push to test switch for mandated code compliance testing.
- 4.8V Long-life, maintenance-free, rechargeable NiCd battery (EM models only).
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 120-minute emergency illumination.
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.

| CATALOG NUMBER | INPUT WATTS (W) | | INPUT AMPS (A) | |
|---------------------|-----------------|------|----------------|-------|
| | 120V | 277V | 120V | 277V |
| RPD-RED/BB/2C/SDT | 3.2 | 3.6 | 0.031 | 0.019 |
| RPD-GREEN/BB/2C/SDT | 3.8 | 4.4 | 0.033 | 0.017 |

WARRANTY / LISTING

- Five year warranty on all electronics and housing. Battery prorated for five years.
- UL listed for damp locations (0° – 50°C).
- Meets UL924, NFPA101 Life Safety Code, NEC, OSHA, Local and State Codes.
- Certified to CEC under Title 20 Regulations

STANDARD



OPTIONAL



FIXTURE ORDERING INFORMATION EXAMPLE: RPDBB3RAA-SDT

| SERIES | OPERATION | NO. OF FACES | LETTER COLOR | HOUSING COLOR | FACE PANEL | OPTIONS |
|--------|---|--|------------------|----------------------------------|----------------------------------|--|
| RPD | BB Battery Backup AC AC Only RE Remote with Central Battery | 1 Single Face 2 Double 3 Universal Single/Double | R Red G Green | A Aluminum W White B Black | A Aluminum W White B Black | SDT Self-Diagnostics ¹ 2C-120 Dual Circuit with 120V input ² 2C-277 Dual Circuit with 277V input ² TP Tamper-Proof USA Assembled In USA |

Special voltage options available. Check with your Signtex Lighting Representative.

¹ Available only with EM units
² Available only with AC units.

| |
|------------|
| PROJECT: |
| TYPE: |
| CATALOG #: |

RAPIER
Series RPD
REV #: RPD.03.26.03



DIMENSIONS

