

## New York City Approved LED Exit & Emergency Combo

### FEATURES

- Adjustable 1.5W square LED lampheads with long lasting & efficient ultra bright white LEDs.
- Field installable 3rd emergency lighting head.
- Knockouts provided on sides of unit to relocate lamp heads.
- High performance chrome-plated metallized reflector and plastic lens for optimal light distribution.
- Ultra bright, energy efficient, long life Red LEDs.
- New York City compliant 8" EXIT letters.
- Knockouts on the back for wall mount.
- Mounting hardware provided for ceiling (2-head model) or end mount.
- Knockouts provided for conduit feed applications.
- Durable, powder-coated 20-gauge steel construction in white or black finish.
- Injection-molded, engineering grade, high-impact, thermoplastic heads.
- Field removable steel knockout chevron directional indicators on exit face

### ELECTRICAL

- Dual 120/277 voltage.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 9.6V maintenance-free, rechargeable NiCd battery.
- Internal solid-state transfer switch automatically connects the internal battery to LED board and lamp heads for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery
- Remote capable standard.

MODEL NUMBER	INPUT WATTS (W)		INPUT AMPS (A)		BATTERY	REMOTE CAPACITY
	120V	277V	120V	277V		
CNY-BB-3RW3	5.2	6.2	0.06	0.04	9.6V	1.5W-3W

### WARRANTY / LISTING

- Five year warranty on all electronics and housing. Batteries prorated for two (lead acid) / five (NiCd) years.
- Meets UL924, NFPA101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL listed for wet locations (0°C – 50°C)
- NYC Approved

### Fixture Ordering Information Example: CNYBB3RW3

CNY	BB	3	R	W	3
SERIES	OPERATION	NO. OF FACES	LETTER COLOR	HOUSING COLOR	NO. OF HEADS
CNY	BB Battery Unit	3 Universal Single/Double	R Red	W White	2 2 Heads 3 3 Heads

PROJECT:
TYPE:
CATALOG #:

## GUARDLITE

**Series CNY**

REV #: CNY.01.26.01



### STANDARD



### DIMENSIONS

