

New York City Compliant Recessed Edgelit Aluminum Exit

FEATURES

- Ultra bright, energy efficient, long life Red LED exit sign illumination.
- UV-stabilized ultra-clear acrylic edgelit panel provides consistent, uniform illumination.
- Double face utilizes factory installed silver or white mylar background panel.
- New York City compliant 8" EXIT letters.
- Compatible with drywall or drop ceiling mount installations. (Bar hangers included).
- Premium-grade, extruded aluminum housing.
- Extruded aluminum trim assembly is easily detachable from below, providing accessibility for service or maintenance.
- Available in black or white powder-coated finishes.
- Self-adhesive chevron appliques and guide template provided for directional indication
- **Options:**
 - **REC:** 12/24VDC input for Central Storage Battery systems.
 - **REP:** 48-60VDC for POE or DC power distribution systems.
 - **SDT:** Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meets electrical and life safety codes.
 - **WM:** Allows for the unit to be wall recessed mounted

ELECTRICAL

- Dual 120/277 voltage standard.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 4.8V long life, maintenance-free, rechargeable NiCd battery (EM models only).
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

MODEL	INPUT WATTS (W)					INPUT AMPS (A)				
	120V	277V	208V	220V	240V	120V	277V	208V	220V	240V
NYR-EM / SPV	3.6	4.0	3.9	3.93	3.98	0.030	0.020	0.023	0.022	0.021
NYR-SDT	3.6	4.0	-	-	-	0.030	0.020	-	-	-

WARRANTY / LISTING

- Five year warranty on all electronics and housing. Battery prorated for five years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL Listed for damp locations (0°C – 50°C).

STANDARD



OPTIONAL



FIXTURE ORDERING INFORMATION EXAMPLE: NYR-BB-1RCA-SDT

SERIES	OPERATION	NO. OF FACES	LETTER COLOR	PANEL	TRIM PLATE	OPTIONS
NYR	BB Battery Backup NB No Battery(AC Only) REC Remote w/ Central Battery System REP Remote DC Power From Power Supply or POE system	1 Single Face 2 Double Face	R Red	C Clear ¹ M Mirror W White	W White B Black A Aluminum	SDT Self-Diagnostics ² WM Wall Mount ¹

¹ With single face only.

² Available only with BB units.

PROJECT:
TYPE:
CATALOG #:

GUARDLITE

Series NYR

REV #: NYR.02.26.02

