

# High-Power LED Indoor Polycarbonate Remote Head

## FEATURES

- Ultra-bright, energy efficient, long-life White LED adjustable lamp heads provide up to 100-ft center-to-center spacing with a 6-ft path of egress at 15-ft mounting height.
- 6.0 watt (12 LEDs x 0.50 watt) per head.
- Adjustable glare-free PAR-Type lamp heads with allinclusive lamp, reflector and lens assembly.
- Powered from low voltage power source with low voltage wiring (not provided).

## MOUNTING

- Universal mounting adapter plate included. Mounts to single gang switch box.
- Distance of maximum run is determined by system voltage, wire gauge and total maximum wattage on the run.
- Suitable for wall or ceiling mount.
- Injection-molded, engineering grade, 5VA flame retardant, high-impact resistant, thermoplastic in white or black finish.

## FIXTURE COMPATIBILITY TABLE

Refer to individual specification sheets to confirm remote load capacity.

EBU & EXIT MODELS			
EML	ELP	RHO	CLP
CXT	RMC	CWL	HLC
CENTRAL BATTERY MODELS			
CBM	CBL	CBE	

## CODES

- UL Listed for damp locations (0°C – 50°C).
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.

## WARRANTY

- 5 year total customer satisfaction warranty.  
For details see Signtex product catalog technical data section.

## FIXTURE ORDERING INFORMATION EXAMPLE: HPRRB2B

HPR	RB	2	B
SERIES	OPERATION	LAMP HEADS	HOUSING COLOR
HPR	RB	1 Single Head	(Blank) White
	RE	2 Double Head	B Black

PROJECT:

TYPE:

CATALOG #:

**PATHLITE**  
**Series HPR**  
REV #: HPR.09.25.01



## DIMENSIONS

