

High-Power LED Outdoor Polycarbonate Remote Head

FEATURES

- Ultra-bright, energy efficient, long-life White LED adjustable lamp heads provide up to 100-ft center-to-center spacing with a 6-ft path of egress at 15-ft mounting height.
- 6.0 watt (12 LEDs x 0.50 watt) per head.
- Adjustable glare-free PAR-Type lamp heads with allinclusive lamp, reflector and lens assembly.
- Powered from low voltage power source with low voltage wiring (not provided).

MOUNTING

- Universal mounting adapter plate included. Mounts to single-gang switch box.
- Distance of maximum run is determined by system voltage, wire gauge and total maximum wattage on the run.
- Suitable for wall or ceiling mount.
- Available in engineering grade, high-impact resistant polycarbonate housing.
- Sealed and gasketed in standard gray or black finish.

FIXTURE COMPATIBILITY TABLE

Refer to individual specification sheets to confirm remote load capacity

EBU & EXIT MODELS			
CAD	CAL	CAR	CWL
DXR	RMR	CEM	IND
HLE	HLC		
CENTRAL BATTERY MODELS			
CBM	CBL	CBE	

CODES

- UL Listed for wet locations (-30°C – 50°C).
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.

WARRANTY

- 5 year total customer satisfaction warranty.
For details see Signtex product catalog technical data section.

FIXTURE ORDERING INFORMATION EXAMPLE: HPORB2B

SERIES	OPERATION	LAMP HEADS	COLOR
HPO	RB Powered from EBU or EXIT Combo RE Powered from Central Battery System	1 Single Head 2 Double Head	(Blank) Gray B Black

PROJECT:

TYPE:

CATALOG #:

PATHLITE
Series HPO
REV #: HPO.09.25.01



DIMENSIONS

